



**NOTES:**

1. STEEL PROTECTION BARRIERS TO BE INSTALLED WHEN TRANSMISSION POLES ARE LOCATED LESS THAN 5' FROM BACK OF CURB OR WHEN NO CURB EXISTS IN PARKING LOTS OR SPEED RESTRICTED STREETS WITH 15MPH MAX SPEED LIMIT.
2. IF MAX SPEED LIMIT IS HIGHER, REFER STD-D6 FOR CONCRETE PROTECTION BARRIERS.
3. BARRIERS ON SIDES NOT ACCESSIBLE TO VEHICLES MAY BE OMITTED.
4. PROVIDE ADEQUATE CLEARANCE FOR EQUIPMENT ITEMS SUCH AS SWITCH OPERATING HANDLES.
5. BARRIERS TO BE PAINTED WITH YELLOW STREET MARKING PAINT.
6. CALL BEFORE YOU DIG AT (800) 227 2600 PRIOR TO THE COMMENCEMENT OF EXCAVATING ACTIVITIES.

NOT TO SCALE

DRAWING INFO.		
DRAWN	04/01/03	JLH
DESIGNED	04/01/03	JLH
CHECKED	04/01/03	SA
APPROVED	04/01/03	SA
	DATE	BY
REV. 1	11/12/08	DP



VEHICULAR PROTECTION BARRIERS  
FOR TRANSMISSION POLES